



CTX-52 Gelacid

DESCRIPTION:

A detergent cleaner formulated for the elimination of calcareous encrustations, organic residues and mineral sediments which form over time and adhere to the surfaces of the swimming pool.

PROPERTIES:

| | |
|------------------|--|
| Appearance | Thick liquid of gelatinous consistency |
| Colour | Purplish red |
| Density | 1,05 – 1,09 g/cm ³ |
| pH | 0 |

CHARACTERISTICS:

Completely dissolves calcareous deposits and metals oxide stains.

Gives off no smoke or vapours annoying to the user.

Applicable physically by brush or roller on vertical surfaces, which means product goes further than the commonly used cleaning liquids.

Its consistency means that it adheres to the walls, thus avoiding the formation of channels and abraded material in cement swimming pools.

Application by brush allows zones to be reached where the dirtiness may adhere more firmly (angles, corners, etc.), without detriment to the other surfaces cleaned previously.

Easily rinsed down with abundant water under pressure.

| | | |
|---|---|---|
|  | <p>Fluidra Comercial España Pintor Velázquez, 10 08213 Polinyà (Barcelona) Spain Tel: 93 713 50 60 Fax: 93 713 41 11 www.certikin.com</p> |  |
|---|---|---|

La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.



DOSAGE AND INSTRUCTIONS FOR USE:

Empty the pool. Use water to wet the surface to be cleaned and apply the product directly, undiluted, using a brush or plastic roller. Leave the product to impregnate the surface for about 1/2 hour, then rinse with plenty of water until it is neutralized.

If the encrustation or stains persist in some zones, treat these zones again by repeating the above operation. In such zones the effect of the product can be enhanced by scrubbing with a brush.

Guideline consumption of the product is some 15 litres for every 100 m³ of swimming pool volume, depending on the degree of dirtiness.



Fluidra Comercial España
Pintor Velázquez, 10
08213 Polinyà (Barcelona) Spain
Tel: 93 713 50 60
Fax: 93 713 41 11 www.certikin.com



La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.